



DESCRIPTION

DUTAPE is a special double sided self-adhesive general purpose tape. It is composed of SBS modified bitumen. A silicon coated release film covers both the faces.

OUTSTANDING FEATURES

- Ideal for hot climate and tropical conditions
- Resistance to high temperatures
- Excellent resistance to chemical attack
- High mechanical strength
- Rot proof and self-sealing
- High resistance to UV rays and weathering
- Easy application

SPECIFICATION COMPLIANCE

DUTAPE membranes exceed the requirements of ASTM, UAETc and other relevant international standards.

MAIN USES

DUTAPE is designed to:

- General purpose, double sided waterproof sealing strip from non-exposed applications
- For use of fixing bituminous protection boards, **DUBOARD** on the butt joints

DUTAPE

DOUBLE SIDED SELF-ADHESIVE TAPE



QUALITY ASSURANCE AND WARRANTY

Duproof is an ISO 9001 Quality Assured Company and DUTAPE carries a material warranty against any manufacturing defects.



DUTAPE (DOUBLE SIDED SELF-ADHESIVE TAPE)

ISS 1/4/17, REV 0

METHOD OF APPLICATION

DUTAPE are simply applied by peeling away the silicon release film and applying the bottom adhesive face on to the bitumen membranes or any other relevant substrate, and roll firmly to ensure complete adhesion without creases or voids. After the tape is adhered on the bottom surface, gently peel the silicon release film from the top surface and press the protection board firmly on to the top adhesive surface.

DUTAPE is recommended to apply at temperatures above 5°C. During cold conditions, place tape between 20°C and 30°C at least 1 hour before application. **DUTAPE** can be hand or machine applied.

Contact the technical department of your local distributor for advice.

STORAGE

DUTAPE rolls must be kept upright on pallets under shade. **DUTAPE** pallets should not be stacked over each other.

HEALTH AND SAFETY

There are no direct health hazards associated with **DUTAPE** membranes. Normal precautions for hot and volatile substances should be observed during application. Refer to our MSDS sheets for advice.

GENERAL DATA

Thickness	(mm)	1.5
Roll length	(m)	15
Tape width (Available)	(cm)	10, 15, 20, 25, 30, 50
Coating		SBS-modified self-adhesive bitumen
Top		Siliconized removable foil / paper
Bottom		Siliconized removable foil / paper

Tolerances on nominal values shown are as per UEAtc directives for polymer modified bitumen membranes. These data are correct at the time of printing but may be changed without any prior notice subject to clients requirements availability of raw materials or other conditions. This data sheet supersedes all previous publications pertaining to this product. All reasonable care has been taken in preparing this document, which to the best of our knowledge is accurate and true. Recommendations and suggestions are made in good faith and should only be considered for general guidance. No liability is assumed or taken by us in relation to the application, as usage conditions and any labour involved are beyond our control.